

Operator's Manual PB-760LN H/T Power Blower

▲ WARNING

The engine exhaust from this product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

WARNING



Read and understand all provided literature before use. Failure to do so could result in serious injury.

Note: This product complies with CAN ICES-2/NMB-2.

TABLE OF CONTENTS

Introduction	3
Servicing Information	
Parts and Serial Number	
Service	4
ECHO Consumer Product Support	4
Product Registration	
Additional Literature	
Safety	
Manual Safety Symbols and Important Information	5
International Symbols	
Personal Condition and Safety Equipment	
Equipment	
Emission Control (Exhaust & Evaporative)	
EPA Emissions Control Information	
Description	
Contents	
Assembly	
Install Blower Pipes/Stick Handle	
Install Blower Pipes	
Operation	
Fuel	
Starting Cold Engine	
Starting Warm Engine	
Stopping Engine	
Operating Blower	
Maintenance	
Skill Levels	
Maintenance Intervals	33
Air Filter	
Fuel Filter	35
Spark Plug	36
Cooling System	
Exhaust System	
Carburetor Adjustment	39
Throttle Cable Adjustment (PB-760T only)	
Troubleshooting	
Storage Long Term Storage (Over 30 Days)	
Specifications	
Product Registration	46

INTRODUCTION

Specifications, descriptions, and illustrative material in this literature are as accurate as possible. Specifications are subject to change without notice. Illustrations might include optional equipment and accessories, and might not include all standard equipment. Your equipment might appear slightly different than pictured equipment.



Read and understand all provided literature. Literature contains specifications and information for safety, operation, maintenance, storage, and assembly specific to this product. Scan QR codes for more information.



For additional literature, including safety manuals where applicable, or questions regarding terms used in this manual, visit:

https://www.echo-usa.com/manuals

OR






https://www.shindaiwa-usa.com/manuals

SERVICING INFORMATION

Parts and Serial Number

Genuine ECHO parts and assemblies for your ECHO products are available only from an Authorized ECHO Dealer. When you do need to buy parts, always have the model number and serial number of the unit with you. For future reference write them in the space provided below.



Model No.	Serial No.	

Service

Service of this product during the warranty period must be performed by an Authorized ECHO Service Dealer. For the name and address of the Authorized ECHO Service Dealer nearest you, ask your retailer or call: 1-800-432-ECHO (3246). Dealer information is also available on our Web Site www.echo-usa.com. When presenting your unit for Warranty service/repairs, proof of purchase is required.

ECHO Consumer Product Support

If you require assistance or have questions concerning the application, operation, or maintenance of this product, call the ECHO Consumer Product Support Department at 1-800-432-ECHO (3246) from 8:00 a.m. to 5:00 p.m. (Central Standard Time) Monday through Friday. Before calling, please know the model and serial number of your unit.

Product Registration

Register your ECHO equipment online at www.echo-usa.com or by filling out the product registration sheet included in this manual. Registering your product confirms warranty coverage and provides a direct link to ECHO if we find it necessary to contact you.

Additional Literature

In addition to finding information online, information is available from your Authorized ECHO Service Dealer, or by contacting ECHO Incorporated, 400 Oakwood Road, Lake Zurich, IL 60047, 1-800-432-ECHO (3246).

SAFETY

Manual Safety Symbols and Important Information

Throughout this manual and on the product itself, you will find safety alerts and helpful, informational messages preceded by symbols or key words. The following is an explanation of those symbols and key words and what they mean to you.

▲ DANGER

The safety alert symbol accompanied by the word "DANGER" calls attention to an act or condition which WILL lead to serious personal injury or death if not avoided.

WARNING

The safety alert symbol accompanied by the word "WARNING" calls attention to an act or condition which CAN lead to serious personal injury or death if not avoided.

A CAUTION

The safety alert symbol accompanied by the word "CAUTION" calls attention to an act or condition which might lead to minor or moderate personal injury if not avoided.

NOTICE

The enclosed message provides information necessary for the protection of the unit.

Note: This enclosed message provides tips for use, care and maintenance of the unit.



CIRCLE AND SLASH SYMBOL

This symbol means the specific action shown is prohibited. Ignoring these prohibitions can result in serious or fatal injury.

International Symbols

Symbol	Description	Symbol	Description
	Read and Understand the Operator's Manual	Ŧ	Carburetor Adjustment - High Speed Mixture
	Wear Eye, Ear and Head Protection	T	Carburetor Adjustment - Idle Speed
	Wear Hand Protection	L	Carburetor Adjustment - Low Speed Mixture
À	Safety/Alert	STOP	Stop Switch
stilliushitu.	Hot Surface	+	Fuel and Oil Mixture
A	Idle speed	*	Fast speed
	Finger severing	•	Purge Bulb
	DO NOT Allow Flames or Sparks Near Fuel	Ignition ON OFF	Ignition ON / OFF

Symbol	Description	Symbol	Description
3	DO NOT Smoke Near Fuel	1	Choke Control "COLD START" Position (Choke Closed)
+	Choke Control "RUN" Position (Choke Open)	*	Wear Slip Resistant Footwear
		Beware of thrown objects	
.09 (50ft)		Keep Bystanders and Helpers Away 15 m (50 ft.).	

Note: Not all symbols will appear on your unit.



Personal Condition and Safety Equipment

WARNING

Cancer and Reproductive Harm www.P65Warnings.ca.gov

WARNING



The muffler or catalytic muffler and surrounding cover may become extremely hot. Always keep clear of exhaust and muffler area, otherwise serious personal injury might occur.

WARNING

Users of this product risk injury to themselves and others if the unit is used improperly and/or safety precautions are not followed. Proper clothing and safety gear must be worn when operating unit.

Physical Condition

Your judgment and physical dexterity may not be good:

- · If you are tired or sick
- If you are taking medication
- If you have taken alcohol or drugs

Operate unit only if you are physically and mentally well.

Eye Protection

WARNING

- ◆ Eye protection that meets ANSI Z87.1 or CE requirements must be worn whenever you operate the unit.
- For additional safety, a full-face shield can be worn over safety glasses or goggles to provide protection from sharp branches or flying debris.

Hand Protection

Wear sturdy, no-slip, rubber work gloves to improve your grip on the handles. Gloves also provide protection against cuts and scratches, cold environments, and reduce the transmission of machine vibration to your hands.

Hearing and Ear Protection

ECHO recommends wearing personal protective equipment whenever unit is used.

Breathing Protection

Operators who are sensitive to dust or other common airborne allergens may need to wear a dust mask to prevent inhaling these materials while operating unit. Dust masks can provide protection against dust, plant debris, and other plant matter such as pollen. Make sure the mask does not impair your vision, and replace the mask as needed to prevent air restrictions.

Proper Clothing

Wear snug-fitting, durable clothing:

- · Pants should have long legs, shirts should have long sleeves.
- · DO NOT WEAR SHORTS.
- DO NOT WEAR TIES, SCARVES, JEWELRY, or clothing with loose or hanging items that could become entangled in moving parts or surrounding growth.
- Keep clothing buttoned or zipped, and keep shirt tails tucked in.
- · Wear sturdy work shoes with nonskid rubber soles.
- DO NOT WEAR OPEN TOED SHOES.
- DO NOT OPERATE UNIT WITH BARE FEET.

Keep long hair away from engine and air intake. Retain hair with cap or net.

Heavy protective clothing can increase operator fatigue, which may lead to heat stroke. Schedule heavy work for early morning or late afternoon hours when temperatures are cooler.

WARNING

The components of this machine generate an electromagnetic field during operation, which can interfere with some pacemakers. To reduce the risk of serious or fatal injury, persons with pacemakers should consult with their physician and the pacemaker manufacturer before operating this machine. In the absence of such information, ECHO does not recommend the use of this machine by anyone who has a pacemaker.

Extended Operation and Extreme Conditions

A CAUTION

Prolonged exposure to cold and/or vibration can result in injury. Read and follow all safety and operation instructions to minimize risk of injury. Failure to follow instructions can result in painful wrist/hand/arm injuries.

It is believed that a condition called Raynaud's Phenomenon, which affects the fingers of certain individuals, may be brought about by exposure to vibration and cold. Exposure to vibration and cold may cause tingling and burning sensations, followed by loss of color and numbness in the fingers. The following precautions are strongly recommended, because the minimum exposure, which might trigger the ailment, is unknown.


- Keep your body warm, especially the head, neck, feet, ankles, hands, and wrists.
- Maintain good blood circulation by performing vigorous arm exercises during frequent work breaks, and also by not smoking.
- Limit the hours of operation. Try to fill each day with jobs where operating the unit or other hand-held power equipment is not required.
- If you experience discomfort, redness, and swelling of the fingers followed by whitening and loss of feeling, consult your physician before further exposing yourself to cold and vibration.

Repetitive Stress Injuries (RSI)

It is believed that overusing the muscles and tendons of the fingers, hands, arms, and shoulders may cause soreness, swelling, numbness, weakness, and extreme pain in those areas. Certain repetitive hand activities may put you at a high risk for developing a Repetitive Stress Injury (RSI). An extreme RSI condition is Carpal Tunnel Syndrome (CTS), which could occur when your wrist swells and squeezes a vital nerve that runs through the area. Some believe that prolonged exposure to vibration may contribute to CTS. CTS can cause severe pain for months or even years.

To reduce the risk of RSI/CTS, do the following

- Avoid using your wrist in a bent, extended, or twisted position. Instead try to maintain a straight wrist position. Also, when grasping, use your whole hand, not just the thumb and index finger.
- Take periodic breaks to minimize repetition and rest your hands.
- Reduce the speed and force with which you do the repetitive movement.
- Do exercises to strengthen the hand and arm muscles.



 Immediately stop using all power equipment and consult a doctor if you feel tingling, numbness, or pain in the fingers, hands, wrists, or arms. The sooner RSI/CTS is diagnosed, the more likely permanent nerve and muscle damage can be prevented.

DANGER

All over head electrical conductors and communications wires can have electricity flow with high voltages. This unit is not insulated against electrical current. Never touch wires directly or indirectly, otherwise serious injury or death can result.

A DANGER

Do not operate this product indoors or in inadequately ventilated areas. Engine exhaust contains poisonous emissions and can cause serious injury or death.

Read the Manual

 Provide all users of this equipment with literature for instructions on safe operation.

Clear the Work Area

- Clear the area of children, bystanders, and pets. At a minimum, keep all children, bystanders, and pets outside a 15 m (50 ft.) radius; outside the 15 m (50 ft.) zone, there is still a risk of injury from thrown objects. Bystanders should be encouraged to wear eye protection. If you are approached, stop the engine.
- Avoid blowing debris towards people, pets, open windows, or vehicles when using unit.
- Review area to be cleared. Look for potential hazards such as stones or metal objects.

Keep a Firm Grip

 To prevent from dropping the unit, hold the handle in one hand, with thumb and fingers encircling the handle.

Keep a Solid Stance

 Maintain footing and balance at all times. Do not stand on slippery, uneven or unstable surfaces. Do not work in odd positions or on ladders. Do not over reach.

Avoid Hot Surfaces

 Keep exhaust area clear of flammable debris. Avoid contact during and immediately after operation.





Equipment

WARNING

Use only approved attachments. Serious injury can result from the use of a non-approved attachment combination. ECHO Incorporated will not be responsible for the failure of cutting devices, attachments or accessories which have not been tested and approved by ECHO. Read and comply with all safety instructions listed in this manual.

- ◆ Do not attempt to modify this product. Serious injury can result from the use of any modified product.
- ◆ Check unit for loose/missing nuts, bolts, and screws. Tighten and/or replace as needed.
- ◆ Do not use blower if any part is missing or damaged.
- ◆ Have repairs done only by an authorized service dealer.

WARNING

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings.

- ◆ ALWAYS stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit.
- ◆ DO NOT start or operate unit unless all guards and protective covers are properly assembled to unit.
- ◆ NEVER reach into any opening while the engine is running. Moving parts might not be visible through openings.

WARNING

Periodically check fuel system (fuel lines, vent, grommet, fuel tank, and fuel cap) for leaks especially if the unit is dropped. If damage or leaks are found, do not use unit, otherwise serious personal injury or property damage may occur. Have unit repaired by an authorized servicing dealer before using.

EMISSION CONTROL (EXHAUST & EVAPORATIVE)

EPA Emissions Control Information

The emission control system for the engine is EM (engine modification) and, if the second to last character of the Engine Family on the Emission Control Information label (see example) is "B", "C", "K", or "T", the emission control system is EM and TWC (3-way catalast). The fuel tank/fuel

EMISSION CONTROL INFORMATION

ENGINE FAMILY: XERVS.0214KO DISPLACEMENT: 21.2 cc EMISSION COMPLIANCE PERIOD: 300 HOURS THIS ENGINE MEETS U.S.EPA EXIVERY EMISSION REGULATIONS FOR MODEL YEAR XXXX RETER TO OWNER'S MANUAL FOR MAINTENANCE SPECIFICATIONS AND ADJUSTMENTS.

YAMABIKO CORP.

line emission control system is EVAP (evaporative emissions).

An Emission Control Label is located on the engine. (This is an EXAMPLE ONLY, information on label varies by engine FAMILY).


Product Emission Durability (Emission Compliance Period)

The 50 or 300 hour emission compliance period is the time span selected by the manufacturer certifying the engine emissions output meets applicable emissions regulations, provided that approved maintenance procedures are followed as listed in the Maintenance Section of this manual.

DESCRIPTION

PB-760LN H

Locate the safety decal(s) or etching(s) on your unit. Make sure they are legible, and that you understand and follow the instructions. If any cannot be read, replacements can be ordered from your ECHO dealer. Images shown below are for example only. Those on your unit might appear slightly different.




PB-760LN H

- 1. Spark Plug
- 2. Safety Decal
- 3. Spark Arrester Muffler (with or without Catalyst)
- 4. Fuel Tank
- 5. Fuel Tank Cap
- 6. Recoil Starter Handle
- 7. Air Cleaner
- 8. Choke
- 9. Purge Bulb
- 10. Shoulder Harness
- 11. Throttle Position Lever/Stop Switch
- 12. Handle
- 13. Stick Handle
- 14. Blower Pipes
- 15. Flexible Pipe

PB-760LN T

Locate the safety decal(s) or etching(s) on your unit. Make sure they are legible, and that you understand and follow the instructions. If any cannot be read, replacements can be ordered from your ECHO dealer. Images shown below are for example only. Those on your unit might appear slightly different



PB-760LN T

- 1. Spark Plug
- 2. Safety Decal
- 3. Spark Arrester Catalytic Muffler / Muffler
- 4. Fuel Tank
- 5. Fuel Tank Cap
- 6. Recoil Starter Handle
- 7. Air Cleaner
- 8. Choke
- 9. Purge Bulb
- 10. Shoulder Harness
- 11. Handle
- 12. Throttle Position Lever
- 13. Throttle Trigger
- 14. Locking Knob
- 15. Blower Pipes
- 16. Flexible Pipe

CONTENTS

The ECHO product you purchased has been factory pre-assembled for your convenience. Due to packaging restrictions, some assembly may be necessary.

After opening the carton, check for damage. Immediately notify your retailer or ECHO Dealer of damaged or missing parts. Use the contents list to check for missing parts.

PB-760 LN H

- 1 Power Head
- 1 Flex Pipe
- 1 Pipe with swivel
- 1 Straight Pipe
- Straight Pipe with decal
- 1 Quick Start Guide
- 2 Clamps with screws
- 1 Warranty Statement
- Stick Handle
- 1 Bolt 6x25 mm
- 1 Washer 6 mm
- 1 Wing nut
- 1 Intake cover

PB-760 LN T

- 1 Power Head
- 1 Flex Pipe
- 1 Pipe with swivel
- 1 Straight Pipe with silencer
- 1 Straight Pipe
- 1 Quick Start Guide
- 1 Warranty Statement
- 2 Clamps with screws
- 1 Intake cover



ASSEMBLY


PB-760 H

WARNING

Never perform maintenance or assembly procedures with engine running or serious personal injury may result.


Install Blower Pipes/Stick Handle

- Assemble clamps (A) onto both ends of flexible pipe (B).
- Assemble swivel pipe (C) into flexible pipe (B) and tighten clamp (A).




 Assemble flexible pipe (B) to elbow (D) on blower and tighten clamp (A).


Note: A light lubricant may be used to ease assembly of flexible pipe to blower elbow.



- Loosen wing nut (H). Align notches in handle clamp with tabs (F).
- Slide stick handle onto swivel pipe (C). Stick handle (E) should be angled away from operator.
- Position stick handle (E) over metal plate on swivel pipe and adjust for comfortable operation. Tighten wing nut (H).



 Assemble straight pipe (J) onto swivel pipe (C), until you feel light resistance. Do not force connection. Hold swivel pipe and turn straight pipe clockwise, engaging positive locking channels, until connection is firm. Do not force connection.



8. Assemble straight pipe with decal (K) to straight pipe (J) as in step 8.

Note: Blower use will eventually loosen pipe connections. Exclusive positive locking system allows pipes to be tightened. If loosening occurs, remove two straight pipes and install according to instructions 8 & 9.

PB-760 T

WARNING


Never perform maintenance or assembly procedures with engine running or serious personal injury may result.

Install Blower Pipes


 Assemble clamps (A) and (G) onto both ends of flexible pipe (B).


Note: Clamp with cable guide loop (G) fits elbow end of flexible pipe.

Note: A light lubricant may be used to ease assembly of flexible pipe to blower elbow.




Note: Hang handle freely from blower to assure throttle cable is not twisted before installing handle (E).







 Position throttle cable along the outside of elbow. Loosen knob (H) on handle (E). Align notches in handle with tabs (F) and install onto swivel pipe (C) past long ridges in pipe.



- 4. Insert anti-static wire through swivel pipe
- 5. Assemble swivel pipe into flexible pipe and tighten clamp (A).
- 6. Clip throttle cable into throttle cable guide loop (G).
- Move handle (E) to desired position. Tighten knob (H) hand tight.



 Assemble straight pipe (J) onto swivel pipe (C), until you feel light resistance. Do not force connection. Hold swivel pipe and turn straight pipe clockwise, engaging positive locking channels, until connection is firm. Do not force connection.



9. Assemble straight pipe with decal (K) to straight pipe as in step 9.

Note: Blower use will eventually loosen pipe connections. Exclusive positive locking system allows pipes to be tightened. If loosening occurs, remove two straight pipes and install according to instructions 9 &10.

OPERATION

WARNING

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings. Always stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit. Blower housing might contain shredder blades and other sharp edges that can cause serious injuries if touched, even if engine is off and blades are not moving. Wear gloves to protect hands from sharp edges and hot surfaces.

WARNING

Operation of this equipment might create sparks that can start fires around dry vegetation. This unit is equipped with a spark arrester to prevent discharge of hot particles from the engine. Contact local fire authorities for laws or regulations regarding fire prevention requirements.

WARNING

Engine exhaust IS HOT, and contains Carbon Monoxide (CO), a poison gas. Breathing CO can cause unconsciousness, serious injury, or death. Exhaust can cause serious burns. ALWAYS position unit so that exhaust is directed away from your face and body.

WARNING

- This blower should be used for clearing leaves, grass, debris, and dust in yards, gardens, driveways, and parking lots only.
- ◆ Always maintain a direct, clear line of site to the unit and the work being performed.
- ◆ Always be alert for changes in operation of unit.
- Always shut engine off before transporting unit to new location.
- Always secure the unit during transportation to prevent turnover, fuel spillage, and damage to the unit.

Fuel

WARNING

Diesel fuels and alternative fuels, such as E-15 (15% ethanol), E-85 (85% ethanol) or any fuels not meeting ECHO requirements are NOT approved for use in ECHO 2-stroke gasoline engines. Use of diesel or alternative fuels may cause performance problems, loss of power, overheating, fuel vapor lock, and unintended machine operation, including, but not limited to, improper clutch engagement. Diesel or alternative fuels may also cause premature deterioration of fuel lines, gaskets, carburetors and other engine components.

Fuel Requirements

Gasoline - Use 89 Octane [R+M/2] (mid grade or higher) gasoline known to be good quality. Gasoline may contain up to 10% Ethanol (grain alcohol) or 15% MTBE (methyl tertiary-butyl ether). Gasoline containing methanol (wood alcohol) is **NOT** approved. Use of ECHO brand fuel is recommended to extend engine life in all air-cooled 2-stroke and 2/4-stroke hybrid engines.

Two Stroke Oil - A two-stroke engine oil, such as ECHO brand 2-stroke oils, meeting ISO-L-EGD (ISO/CD 13738) and J.A.S.O. <u>FD</u> Standards must be used. ECHO brand 2-stroke oils meet these standards. Engine problems due to inadequate lubrication caused by failure to use an ISO-L-EGD (ISO/CD 13738) and J.A.S.O. M345-<u>FD</u> certified oil will void the two-stroke engine warranty.

▲ WARNING

2-Stroke engine oil contains petroleum distillates and other additives that may be harmful if swallowed. Heated oil can release vapors that can cause flash fire, or ignite with explosive force. Read and follow the oil manufacturer's instructions, and observe all safety warnings and precautions for handling flammable liquids. For more detailed safety and first aid information, visit www.echo-usa.com for a copy of the Material Safety Data Sheet.

- ***** KEEP OUT OF REACH OF CHILDREN.
- If swallowed, do not induce vomiting. CALL PHYSICIAN OR A POISON CONTROL CENTER IMMEDIATELY.
- WEAR SAFETY GLASSES when mixing or handling.

- AVOID repeated or prolonged skin contact
- ◆ AVOID inhaling oil mists or vapors.

NOTICE

ECHO brand 2-stroke oils may be mixed at 50:1 ratio for application in all ECHO engines sold in the past regardless of ratio specified in those manuals.

Handling Fuel

A DANGER

Fuel is VERY flammable. Use extreme care when mixing, storing or handling, or serious personal injury may result.

- ◆ Use an approved fuel container. Mark fuel containers as containing 2-stroke mixture fuel.
- ◆ DO NOT smoke near fuel.
- ◆ DO NOT allow flames or sparks near fuel.
- ◆ Fuel tanks/cans may be under pressure. Always loosen fuel caps slowly allowing pressure to equalize.
- ◆ NEVER refuel a unit when the engine is HOT or RUNNING!
- DO NOT fill fuel tanks indoors. ALWAYS fill fuel tanks outdoors over bare ground.
- ◆ DO NOT overfill fuel tank. Wipe up spills immediately.
- Securely tighten fuel tank cap and close fuel container after refueling.
- ◆ Inspect for fuel leakage. If fuel leakage is found, do not start or operate unit until leakage is repaired.
- ◆ Use caution when handling fuel. Mix and pour fuel outdoors where there are no sparks and flames. Slowly remove the fuel cap only after stopping the engine and allowing the unit to cool. Do not smoke while fueling or mixing fuel. Move the unit at least 10 feet (3 m) from the fueling point before starting the engine.

▲ DANGER

Gasoline vapor is heavier than air, and can travel along the ground to nearby sources of ignition such as electrical motors, pilot lights, and hot or running engines. Vapors ignited by an ignition source can flash back to the fuel container, resulting in an explosion, fire, serious or fatal injuries, and extensive property damage.

Mixing Instructions

- Fill an approved fuel container with half of the required amount of gasoline.
- 2. Add the proper amount of 2-stroke oil to gasoline.
- 3. Close container and shake to mix oil with gasoline.
- 4. Add remaining gasoline, close fuel container, and remix.

Fuel to Oil Mix – 50:1 Ratio			
US		Metric	
Gas	Oil	Gas	Oil
gal.	fl.oz.	L	СС
1	2.6	5	100
2	5.2	10	200
5	13	25	500

NOTICE

Spilled fuel is a leading cause of hydrocarbon emissions. Some states may require the use of automatic fuel shut-off containers to reduce fuel spillage.

 Empty the fuel tank prior to storing the unit. Return unused fuel to an approved fuel storage container.

Storage - Fuel storage laws vary by locality. Contact your local government for the laws affecting your area. As a precaution, store fuel in an approved, airtight container. Store in a well-ventilated, unoccupied building, away from sparks and flames.

NOTICE

Stored fuel ages. Do not mix more fuel than you expect to use in 30 days, 90 days when a fuel stabilizer is added.

NOTICE

Stored two-stroke fuel may separate. ALWAYS shake fuel container thoroughly before each use.

NOTICE

Used oil and gasoline, and soiled towels are hazardous waste materials. Disposal laws vary by locality.

Starting Cold Engine

- Recoil starter: Use short pulls only 1/2- 2/3 of rope length for starting. Do
 not allow the rope to snap back in. Always hold the unit firmly.
- (PB-760H): Rotate spring loaded throttle arm downward to a comfortable operating position.
- 1. Throttle Position Lever

Move throttle position lever (A) to IDLE position.



Move choke (C) UP to COLD START (►) position.

3. Purge Bulb

Pump purge bulb (D) until fuel is visible. Pump bulb an additional 4 or 5 times.

Recoil Starter

Pull recoil starter handle (E) until engine fires, or a maximum of 5 pulls


Choke

After engine fires (or 5 pulls), move choke lever back to RUN ($| \downarrow |$) position, then pull starter handle/rope until engine starts and runs. Allow unit to warm up at idle for several minutes.

Note: If engine does not start with choke in "RUN" position after 5 pulls, move choke to COLD START () position, and repeat steps 4- 5.

Throttle Position Lever

Allow engine to warm up for several minutes before use.




7. Throttle Position Lever

After engine warm-up, move throttle position lever gradually to increase engine RPM to desired operating speed.

Starting Warm Engine

The starting procedure is the same as Cold Start except DO NOT close the choke.v

Throttle Position Lever
 Move throttle position lever (A) to IDLE position.




2. Purge Bulb

Pump purge bulb (D) until fuel is visible. Pump bulb an additional 4 or 5 times.

3. Recoil Starter

Pull recoil starter handle (E) and engine should start. Do not use choke (C)



Note: If engine does not start after 5 pulls, use cold start procedures.


Stopping Engine

- PB-760 H

1. Throttle Position Lever

Move throttle position lever (A) to IDLE position and allow engine to return to idle before shutting off engine.

Throttle Position Lever
 Move throttle position lever (A) to "O" (STOP) position.



- PB-760 T

1. Throttle Position Lever

Release throttle trigger. Move Throttle Position Lever (A) forward to idle position and allow engine to return to idle before shutting off engine.

2. Throttle Position Lever

Move Throttle Position Lever (A) all the way forward to STOP position.

WARNING

If engine does not stop when stop switch is moved to STOP position, close choke - COLD START position - to stall engine. Have your dealer repair stop switch before using unit again.

Operating Blower

WARNING

Engine exhaust IS HOT, and contains Carbon Monoxide (CO), a poison gas. Breathing CO can cause unconsciousness, serious injury, or death. Exhaust can cause serious burns. ALWAYS position unit so that exhaust is directed away from your face and body.

A WARNING

Always wear safety glasses, hearing protection and a face filter mask or serious personal injury may result. Do not point the blower pipe in the direction of people or pets.

NOTICE

Use reduced speed only when performing light-duty tasks or to comply with local noise regulations. Continuous low speed operation may allow fuel/oil residue to build-up on the piston and cause rapid build-up of carbon on the spark arrester screen, resulting in overheating and engine damage. To reduce harmful build-up, run engine at wide open throttle for at least 5 minutes every hour, and inspect/clean the spark arrester screen after approximately 40 hours of operation.

Read the Safety Section carefully.

NOTICE

To avoid engine damage due to over-revving, do not block blower pipe.

- Use only during appropriate hours. Contact your local government for the ordinances affecting your area.
- 2. To reduce sound levels, limit the number of pieces of equipment used at any one time.
- 3. Allow the engine to warm up at a fast idle for a few minutes.

4. PB-760 H

Set engine speed with throttle position lever (A).

PB-760 T

Control engine speed with throttle trigger (B), or for continuous use, set engine speed with throttle position lever (A).

5. Use lower speed to blow dry leaves from walks, patios and drives. Use rakes and brooms to loosen debris before blowing.



PB-760 H

- Additional speed may be necessary to clean grass and leaves from a lawn or flower bed.
- Higher speed may be necessary to move gravel, dirt, snow, bottles or cans from a driveway, street, parking lot or stadium.
- 8. Always stop unit using stop engine procedure.

Note: Never use a higher speed setting than necessary to perform a task. Remember, the higher the engine speed, the louder the blower noise.

For Operator Comfort in Cold Weather Operation:

A WARNING


This product should not be used in temperatures below 15° F (-9° C) otherwise damage to the fuel lines may occur.

1. Remove back cushion (A) from frame.



- 2. Install intake cover (B) on frame over air intake.
- 3. Install back cushion (A) to frame over intake cover.

Note: Blower performance may be reduced slightly.



MAINTENANCE

WARNING

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings. Always stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit. Allow the unit to cool before performing maintenance or adjustments. Wear gloves to protect hands from sharp edges and hot surfaces.

A WARNING

Operating a poorly maintained unit can result in serious injuries to operator or bystanders. Always follow all maintenance instructions as written, otherwise serious personal injury can result.

Your unit is designed to provide many hours of trouble free service. Regular scheduled maintenance will help your unit achieve that goal. If you are unsure or are not equipped with the necessary tools, we recommend that you take your unit to a Servicing Dealer for maintenance. To help you decide whether you want to DO-IT-YOURSELF or have the Dealer do it, each maintenance task has been graded. If the task is not listed, see your Dealer for repairs.

NOTICE

The use of emission control components other than those specifically designed for this unit is a violation of federal law.

Skill Levels

Level 1 = Easy to do. Common tools may be required.

Level 2 = Moderate difficulty. Some specialized tools may be required.

Level 3 = See your dealer.

Click HERE or go to http://www.echo-usa.com/products/maintenance-kit or

HERE https://www.shindaiwa-usa.com/you-can.aspx

Maintenance Intervals

COMPONENT/SYSTEM	MAINTENANCE PROCEDURE	SKILL LEVEL	
Daily or Before Use			
Air Filter	Inspect/Clean ¹	1	
Choke Shutter	- Inspect/Clean		
Fuel System	Inspect		
Cooling System	Inspect/Clean	2	
Recoil Starter Rope	Inspect/Clean ¹	1	
Screws/Nuts/Bolts	Inspect/Tighten/Replace ¹		
Every Refuel			
Fuel System	Inspect ¹	1	
Cooling System	Inspect/Clean	2	
3 Months			
Air Filter	Replace ¹		
Fuel Filter	Inspect ¹	1	
Fuel Cap Gasket	Inspect		
Spark Plug	Inspect/Clean/Replace ¹	2	
Muffler Spark Arrester	Inspect Clean/Replace		
Cylinder Exhaust Port	Inspect/Clean/De-carbon		
Yearly			
Fuel Filter	Inspect/Replace ¹	1	
Fuel Cap Gasket	Replace ¹		

IMPORTANT NOTE - Time intervals shown are maximum. Actual use and your experience will determine the frequency of required maintenance.

MAINTENANCE PROCEDURE NOTES:

¹Replacement is recommended based on the finding of damage or wear during inspection.

Air Filter


Level 1.

Parts Required: TUNE UP KIT.

- Close choke (COLD START() position). This prevents dirt from entering the carburetor throat when the air filter is removed. Brush accumulated dirt from air cleaner area.
- Remove air filter cover, air filter, retainer, and foam pre-filter. Brush dirt from inside cover.

Foam Pre-Filter:

- Clean foam filter (A) in water/ detergent solution and rinse with clean water.
- Wrap the filter in a clean, dry cloth and squeeze (do not wring) dry. Allow to dry completely before reuse. Do not oil.



Air Filter:

- Lightly brush debris from air filter (B).
- Replace filter if it is damaged, very dirty, or the rubber sealing edges are deformed.
- If filter can be reused, be certain it fits tightly in the air filter cavity, and is installed with the original side out.
- 3. Assemble components in reverse order.

Fuel Filter

Level 1.

Parts Required: TUNE UP KIT.

A DANGER

Fuel is VERY flammable. Use extreme care when mixing, storing or handling, or serious personal injury may result.

 Use a clean rag to remove loose dirt from around fuel cap and empty fuel tank.



NOTICE

Do not damage fuel line while removing fuel filter from tank or line.

- Pull the fuel filter from the tank.
- Do not remove the wire coil clamp to remove the fuel filter. Pinch the fuel filter with the fingers on one hand and the fuel line with the other hand. Pull and twist slightly to separate.
- 4. Install the new filter with the reverse action.

Note: Federal EPA regulations require all model year 2012 and later gasoline powered engines produced for sale in the United States to be equipped with a special low permeation fuel supply hose between the carburetor and fuel tank. When servicing model year 2012 and later equipment, only fuel supply hoses certified by EPA can be used to replace the original equipment supply hose. Fines up to \$37,500 may be enforced for using an un-certified replacement part.

Spark Plug


Level 2.


Parts Required: TUNE-UP KIT

NOTICE

Use only NGK BPM6Y spark plug (BPMR6Y in Canada) otherwise severe engine damage may occur.

- Remove spark plug and check for fouling, worn and rounded center electrode.
- Clean the plug or replace with a new one. DO NOT sand blast to clean. Remaining sand will damage engine.
- 3. Adjust spark plug gap by bending outer electrode.





Cooling System

Level 2.


Parts Required: None if you are careful.

NOTICE

To maintain proper engine operating temperatures, cooling air must pass freely through the cylinder fin area. This flow of air carries combustion heat away from the engine.

Overheating and engine seizure can occur when:

- Air intakes are blocked, preventing cooling air from reaching the cylinder.
- Dust and grass build up on the outside of the cylinder. This build up insulates the engine and prevents the heat from leaving.




Removal of cooling passage blockages or cleaning of cooling fins is considered "Normal Maintenance." Any failure attributed to lack of maintenance is not warranted.


Cleaning Grill

 Brush accumulated debris from intake grill between backpack frame and blower housing.

Cleaning Cylinder Fins

- Disconnect spark plug lead from spark plug.
- 2. Close the choke to prevent debris entering the engine.
- 3. Remove air filter cover.
- 4. Remove muffler cover (A).
- 5. Remove engine cover (B).
- Clean cylinder fins (C) to allow cooling air to pass freely.
- Install engine cover and muffler cover.
- 8. Install air filter cover.
- 9. Connect spark plug lead.





Exhaust System


Spark Arrester Screen Level 2.

Parts Required: Spark Arrester Screen, Gasket

NOTICE

Carbon deposits in muffler will cause a drop in engine output and overheating. Spark arrester screen must be checked periodically.

- Disconnect spark plug lead from spark plug.
- 2. Remove muffler cover (A).




Note: When cleaning carbon deposits, be careful not to damage the catalytic element inside muffler.


- 4. Install spark arrester screen, gasket, and spark arrester cover.
- 5. Install muffler cover.
- 6. Connect spark plug lead.


Exhaust Port Cleaning Level 2.

Parts Required: As needed: Muffler Gasket

- 1. Remove spark plug lead from spark plug.
- 2. Remove muffler cover and engine cover.
- Place piston at top dead center. Remove muffler (A) muffler gasket (B), and muffler insulator (C).
- Use a wood or plastic scraping tool to clean deposits from cylinder exhaust port.







NOTICE

Never use a metal tool to scrape carbon from the exhaust port. Do not scratch the cylinder or piston when cleaning the exhaust port. Do not allow carbon particles to enter the cylinder.

- 5. Inspect muffler gasket, and replace if damaged.
- 6. Install muffler insulator, muffler gasket and muffler.
- Tighten muffler mounting bolts (or nuts) to 110-150 kgf•cm (95-130 lbf•in).
- 8. Install engine cover and attach spark plug lead.
- Start engine, and warm to operating temperature.
- 10. Stop engine, and re-tighten mounting bolts (or nuts) to specifications.
- 11. Install muffler cover.



Engine Break-In

New engines must be operated a minimum duration of two tanks of fuel break-in before carburetor adjustments can be made. During the break-in period your engine performance will increase and exhaust emissions will stabilize. Idle speed can be adjusted as required.

High Altitude Operation

This engine has been factory adjusted to maintain satisfactory starting, emission, and durability performance up to 1,100 feet above sea level (ASL) (96.0 kPa). To maintain proper engine operation and emission compliance above 1,100 feet ASL the carburetor <u>may</u> need to be adjusted by an authorized ECHO service dealer.

NOTICE

If the engine is adjusted for operation above 1,100 feet ASL, the carburetor must be re-adjusted when operating the engine below 1,100 feet ASL, otherwise severe engine damage may result.



Level 2.

Note: Every unit is run at the factory and the carburetor is set in compliance with emission regulations. Carburetor adjustments, other than idle speed, must be performed by an authorized ECHO dealer.

Idle Adjustment

Before adjustment make sure that:

- Air filter is clean and properly installed.
- · Spark arrester screen and muffler are free of carbon.
- · Blower pipes are installed.
- 1. Start engine, run at idle for one minute.
- Complete warm up by running at full throttle for 5 minutes, operating choke twice to clear air from carburetor chambers.
- Check idle speed and reset if necessary. If a tachometer is available, idle speed screw (A) should be set to the specifications found on "Specifications" Page of this manual. Turn idle screw (A) clockwise to increase idle speed; counter clockwise to decrease idle speed.




Throttle Cable Adjustment (PB-760T only)


Level 1.

If engine idle speed changes when blower pipe is moved, or engine will not reach full wide open throttle speed, adjust throttle cable.

 Loosen handle adjustment knob (C) and tilt Tube Throttle handle forward to expose Adjustment Screw (D).



- 2. Turn Adjustment Screw until Throttle Trigger free play is 4 6 mm (3/16-1/4 in.).
- After adjustment, squeeze and release Throttle Trigger several times to verify Carburetor Throttle Shaft has full range of movement from idle to wide open throttle positions.



TROUBLESHOOTING

▲ DANGER

Fuel vapors are extremely flammable and may cause fire and/or explosion. Never test for ignition spark by grounding spark plug near cylinder plug hole, otherwise serious personal injury may result.

	ENGINE PRO	BLEM TROUE	BLESHOOTING	CHART
Problem	Check	Status	Cause	Remedy
	Fuel at carburetor	No fuel at carburetor	Fuel strainer or fuel line obstructed	Clean or replace See your dealer
Engine starts		No fuel at cylinder	Carburetor	See your dealer
hard or Engine does not start	Fuel at cylinder	Muffler wet with fuel	Fuel mixture too rich	OPEN choke Clean or replace air filter Adjust carburetor See your dealer
Engine starts hard or Engine	Spark at end of plug wire	No spark	Ignition at STOP position Electrical problem Interlock switch	Move ignition away from STOP position. See your dealer
does not start	Spark at plug		Incorrect gap - Covered with carbon - Fouled with fuel - Plug defective	Adjust to 0.65 mm (0.026 in.) Clean or replace plug

	ENGINE PRO	BLEM TROUE	BLESHOOTING	CHART
Problem	Check	Status	Cause	Remedy
	Air filter	Air filter dirty	Normal wear	Clean or replace
Engine	Fuel filter	Fuel filter dirty	Contaminants or residue in fuel	Replace filter or replace fuel
runs, but dies	Fuel vent	Fuel vent plugged	Contaminated fuel	Clean or replace
or	Spark plug	Plug dirty or worn	Normal wear	Clean and adjust or replace
Engine does not	Carburetor	Improper adjustment	Vibration	Adjust
acceler- ate properly	Cooling system	Cooling system dirty or plugged	Extended oper- ation in dirty or dusty locations	Clean
	Spark arrester screen	Spark arrester screen plugged	Normal wear	Replace
Engine does not crank	1	N/A	Internal engine problem	See your dealer

STORAGE

WARNING

During operation the muffler or catalytic muffler and surrounding cover become hot. Always keep exhaust area clear of flammable debris during transportation or when storing, otherwise serious property damage or personal injury may result.

Long Term Storage (Over 30 Days)

A DANGER

Do not store in enclosure where fuel fumes may accumulate or reach an open flame or spark.

Do not store your unit for a prolonged period of time (30 days or longer) without performing protective storage maintenance which includes the following:

- 1. Store unit in a dry, dust free place, out of the reach of children.
- 2. Place the stop switch or lever in the "OFF" position.
- Remove accumulation of grease, oil, dirt and debris from exterior of unit.
- 4. Perform all periodic lubrication and services that are required.
- 5. Tighten all the screws and nuts.
- 6. Drain fuel tank completely. Press purge bulb 6 -7 times to remove remaining fuel from carburetor then drain the tank again. Close choke, start and run the engine until it stops due to lack of fuel.
- 7. Allow engine to cool. Remove the spark plug lead from the spark plug. Remove the spark plug. Pour 7 cc (0.25 oz.) of fresh, clean, two-stroke engine oil into the cylinder through the spark plug hole.
- 8. Pull the recoil starter handle 2-3 times to distribute the oil inside the engine.
- Observe the piston location through the spark plug hole. Pull the recoil handle slowly until the piston reaches the top of its travel and leave it there.
- 10. Install the spark plug. Connect the spark plug lead to the spark plug.
- Remove blower pipe assembly from unit.



SPECIFICATIONS

MODEL	PB-760 H	PB-760 T	
Length (without pipes)	375 mm (14.8 in.)		
Width (without pipes)	535 mm (21.1 in.)	490 mm (19.3 in.)	
Height (without pipes)	475 mm (18.7 in.)		
Weight (dry) (without pipes)	10.0 kg (22.0 lb.)	9.8 kg (21.6 lb.)	
Engine Type	Air-cooled, two-stroke, single cylinder gasoline engine		
Bore	48.0 mm (1.89 in.)		
Stroke	35.0 mm (1.38 in.)		
Displacement	63.3 cc (3.86 in ³)		
Exhaust	Spark arrester muffler or spark arrester muffler with catalyst		
Carburetor	Diaphragm with purge pump		
Ignition System	Flywheel magneto, capacitor discharge ignition type		
Spark Plug	NGK BPM6Y (BPMR6Y in Canada) (Gap 0.65 mm (0.026 in.)		
Fuel	Mixed (Gasoline and Two-stroke Oil)		
Gasoline/Oil Ratio	50:1		
Gasoline	Use 89 Octane unleaded. Do not use fuel containing methyl alcohol, more than 10% ethyl alcohol or 15% MTBE. Do not use alternative fuels such as E-15 or E-85.		
Oil	ISO-L-EGD (ISO/CD 13738) and J.A.S.O. M345- <u>FD</u> , two-stroke, air-cooled engine oil.		
Fuel Tank Capacity	2.02 L (68.3 US fl. oz.)		
Starter System	Automatic Recoil Starter, centrifugal type		
Idle Speed	2,450 RPM		
Wide Open Throttle Speed	6,000 RPM		
Average Air Speed with pipes	79.6 m/sec (178 mph)		

MODEL	PB-760 H	PB-760 T
Maximum Air Speed with pipes	93.7 m/sec (210 mph)	
Air Volume	15.1 m ³ /min. (53	35 ft./min. ³)
Sound Level at 50 ft. dB(A) scale per ANSI B175.2	65 dB(A)	

PRODUCT REGISTRATION

Thank you for choosing ECHO Power Equipment

Please go to http://www.echo-usa.com/Warranty/Register-Your-ECHO to register your new product on-line. It's **FAST** and **EASY!** NOTE: your information will never be sold or misused by ECHO, Incorporated. Registering your purchase enables us to contact you in the unlikely event of a service update or product recall, and verifies your ownership for warranty consideration.

If you do not have access to the Internet, you can complete the form below and mail to:

ECHO Incorporated, Product Registration, PO Box 1139, Lake Zurich, IL 60047.



TRATION CARD :TARJETA DE REGISTRO : CARTE D'ENREGISTREMENT DU PRODUIT

lease Print : Por Favor Enscriba Con Letra De Molde : En Purchasser's Name : Nombre del Comprador : Nom de l'ache

OPCIÓN POR INTERNET: Registrase en la pagina web y adhoren use atalanza los actalanzas observadas adhoren un estamplial la cleardara sobre los nuevos productos ECHÓ y las oferas especaleas. Simplemente visite: www.echo-usacom

OPTION EN LIGNE: Enregistrer en ligne et épargner un finnnel Vous serez informé sur les nouveaux produits ECHO et les mises à jour de produit ainsi que les offres spéciales. Simplement visitez le: www.echo-usa.com

n Lettre Carre 5.V.P.	confidential: Information provided will not be snared of sold
heteur	Primary use of tool: □Professional □ Homeowner □ Rental Equip. Uso primario de la herramienta:□Profesional □ Dueño de casa □ Aquiler Usage principal: □ Profesionnel □ Residential □ Location □ Profesionel □ Programming and property of the profesion of the profe
	to you wan for tecave periodic ECHO product morimation and special oriers by e-mail? □ Yes □ No 2 Desea usted recibir información periodica y ofertas especiales por correo electronico sobre el producte CHO? □ Yes □ No Southaitez-vous recevoir périodicuement de l'information sur les produits
Zip Code : Código Postal : Code Postal	ECHO et les offres spéciales par courrier électronique ? □ Oui □ □ Non Did you visit the ECHO website before purchasing your product? □ Yes □ No
ier Électronique	Visito usted la pagina web ECHO antes de comprar su producto? ☐ Sī ☐ No Avez-vous visité le site d'ECHO avant de procurer votre produit? ☐ Oui ☐ Non
Date of Purchase : Fecha de la Compra : Date de l'achat	What factor(s) most influenced your purchase? Performance
rado : Lieu d'achat	nfluenció más en su comprenció más en su comprenció Dreció Experiencia Anterior Description Marca
al Number : Numero de Serie : No. de série	cteurs) vous a influencé le pl Drix Expérience
it of a service update or product recall and verifies your	nille 🗖 Marque

E-Mail Address : Dirección De Correo Electrónico : Courrie

Phone Number: Número De Teléfono: Téléphone

State: Estado: Province

City: Ciudad: Ville

Where Purchased : Nombre del Almacén donde fue Comprac

Registering your purchase enables us to contact you in the unifiely event of a service update or product recall and verifies your ownership. The event of tass. Effects as compare no specified in contact of most ender case of could use remote come a feature of the service of a revocation de productly verification feet propiedate en case de note of pedida. It can estimate the other activation are permitted the volte activation and expensive and expensive the contact of entitle and any other permitted the volte activations desurrant entitles and entitle of the representations of entitle or the stoped in product of white que vous deele feet to propied entitle or to de perior described.

Serial

Model Number: Numero del Modelo: No. de modéle

X7572270206 02-2012

ECHO Incorporated 400 Oakwood Rd., Lake Zurich, IL 60047 1.800.432.ECHO WWW.ECHO-USA.COM

Address : Dirección : Adresse

P39313001001 - P39313999999 P39413001001 - P39413999999



400 Oakwood Road Lake Zurich, IL 60047 www.echo-usa.com